



SO-H82

Automatic Gyroscopic Mixer



- Intelligently identify the size of the barrel
- Lower clamping plate makes it convenient.
- The pressure plate can rotate
- Suitable for mixing various viscosity canned chemicals
- Different parameters can be adjusted and set.

F and D Technologies

General Manager

Jono Swart

066 214 2275 / 081 712 7980

manager@fanddtechnologies.co.za

Technical Manager

Marius Liebenberg

060 988 8707

technical@fanddtechnologies.co.za

www.fndtech.co.za

info@fanddtechnologies.co.za



SO-H82



- * Mixing time setting: 20seconds – 600seconds (longer time can be customized)
- * Maximum mixing weight: 35KG
- * Maximum mixing barrel height: 95mm-410mm
- * Large barrel mixing speed: 50-100rpm (adjustable)
- * Small barrel mixing speed: 50-150rpm (adjustable)
- * Rotation direction: forward, reverse and single direction mixing modes are optional
- * Barrel type: round/square barrel
- * Maximum specification: diameter 320mm
- * Power supply: 110/220V + 10% – 50/60 HZ
- * Power: 750W
- * Net weight of equipment: 196KG
- * Gross weight: 252KG
- * Equipment size: 830(L)x760(W)x1090(H)
- * Packing size: 885(L)x805(W)x 1200(H)

Product Advantages

1. Intelligently identify the size of the barrel or container and apply different pressures and mixing speeds.
2. The lower clamping plate that can be moved forward makes loading and unloading packaging barrel easy and convenient.
3. The pressure plate can rotate 720 degrees in both directions and the time for both directions can be set.
4. Suitable for mixing various low and medium viscosity canned chemical coatings, inks, etc and liquid slurries.
5. Different parameters can be adjusted and set and manual and automatic modes are easy to maintain and replace.

F and D Technologies

General Manager

Jono Swart

066 214 2275 / 081 712 7980

manager@fanddtechnologies.co.za

Technical Manager

Marius Liebenberg

060 988 8707

technical@fanddtechnologies.co.za

www.fndtech.co.za

info@fanddtechnologies.co.za