



SO-H83

Manual Gyroscopic Mixer

Soruda
索瑞达科技



- Rotary movement, manual clamping and loosening
- Bucket shape: round / square
- Max. bucket diameter: 326mm
- Rotation and revolution are carried out simultaneously

F and D Technologies

General Manager

Jono Swart

066 214 2275 / 081 712 7980

manager@fanddtechnologies.co.za

Technical Manager

Marius Liebenberg

060 988 8707

technical@fanddtechnologies.co.za

www.fndtech.co.za

info@fanddtechnologies.co.za



SO-H83

Soruda 索瑞达



- * Mixing time: 0-300s
- * Mixing capacity: 1-20L
- * Maximum Load: 1-35KG
- * Mixing speed: 150r/min (adjustable)
- * Range of container height: 80-380mm
- * Power source: 220V 110V
- * Power: 750W
- * Net weight: 192KG
- * Gross weight: 242KG
- * Equipment size:
850(L)x760(W)x1070(H)
- * Packing size: 870(L)x810(W)x1210(H)
- * Physical distribution: 20G:
12set/40GP:24set

Product Advantages

1. Manually clamp and release the packaging barrel, simple operation, convenient maintenance and more cost-effective.
2. The lower clamping plate can move forward and position, making it easier and more convenient to put in and take out the packaging barrel.
3. Rotation and revolution are carried out simultaneously and the mixing is more uniform.
4. The fully enclosed design is suitable for different working environments and is safer.
5. This product can be used for mixing canned chemical coatings, inks, etc and liquid slurries.

F and D Technologies

General Manager

Jono Swart

066 214 2275 / 081 712 7980

manager@fanddtechnologies.co.za

Technical Manager

Marius Liebenberg

060 988 8707

technical@fanddtechnologies.co.za

www.fndtech.co.za

info@fanddtechnologies.co.za